

EFUEL 1200W POWER SUPPLY V2



50A 1200W

SPECIFICATIONS

Voltage	100-240V AC
Input AC Frequency	50-60Hz
Output Voltage	15-30V DC±0.5V
Output Current	50A±1A
Current Overload Protection	≤ 51A 500MS
Input Fuse	20A Fuse
LCD Display	Voltage Precision ±0.3V Current Precision ±0.5A
Output Voltage Ripple	<300mV
Power Efficiency	89%
Power Factor	>0.98
Over Temperature Protection	<65°C
Cooling Method	Cooling Fan
Operating Temperature	0-40°C
Operating Humidity	0-90%
Dimensions (LxWxH)	305x170x85mm
Net weight	3.08kg



Worldwide AC Voltage



Power Factor Correction

SK-200015

EFUEL 30A POWER SUPPLY

SPECIFICATIONS

Voltage	100-240V AC
Input AC Frequency	50-60Hz
Output Voltage	12-18V DC±0.5V
Output Current	30A±1A
Current Overload Protection	≤ 31A 500MS
Input Fuse	10A Fuse
LCD Display	Voltage Precision ±0.3V Current Precision ±0.3A
Output Voltage Ripple	< 150mV
Power Efficiency	89%
Power Factor	>0.98
Over Temperature Protection	<65°C
Cooling Method	Cooling Fan
Operating Temperature	0-40°C
Operating Humidity	0-90%
Dimensions (LxWxH)	218x139x59.5mm
Net Weight	1.62kg



30A 540W



Worldwide AC Voltage



Power Factor Correction

SK-200013

AC ADAPTER

PSU-60W 15V 4A

- High Performance Power Supply
- Input: AC100-240V 50/60Hz 1.5A
- Output: DC 15V 4A
- Dimension: 113.5x55.7x32.7mm
- Net Weight: 210g



SK-200008

POWER STRIP

- Five Channels
- Fuse Protected
- With ON/OFF Switch
- USB Power Output: 5V1A
- Dimension: 160x60x41.1mm
- Net Weight: 250g



SK-600009